


Very narrow sliding door solution SL with integrated floor guiding groove

Main features

- lift height 20 mm
- compact space-saving solution with integrated floor guiding groove
- adjustable floor guide included
- release on lock side with parallel drop-down
- automatic compensation to inclined floors
- acoustic isolation of 42 dB (at 7 mm air gap door to floor)
- can be shortened to the next shorter length in stock
- high-quality silicone lip, simple lift height adjustment
- warranty 7 years

Executions

- Planet SL RD/42dB, smoke shielding
- Planet SL FH+RD/42dB, fire-retardant and smoke-shielding
- assembly on top
- refer also to chapter special solutions
- DIN L | DIN R



Scale 1:1



Advertising text

Planet SL RD/42dB, smoke-shielding



Automatic door drop-down seal **Planet SL RD/42dB**, for sound absorption and smoke-shielding sliding doors, release on hinge side, seal lift height up to 20 mm, flush to put in groove or deeper with lip protection. Silicone lip, lateral fastening incl. floor guide. Aluminum profile 21,8×30 mm.

Planet SL FH+RD/42dB, fire-retardant and smoke-shielding



Automatic door drop-down seal **Planet SL FH+RD/42dB**, for sound absorption, smoke-shielding and fire-retardant sliding doors, release on hinge side, seal lift height up to 20 mm, flush to put in groove or deeper with lip protection. Silicone lip, lateral fastening incl. floor guide. Aluminum profile 21,8×30 mm.

Technical specifications

Profile material:	aluminium, 21,8×30 mm
Groove size:	deep 22×30,5 up to 35 mm
Seal height/lift height:	up to 20 mm
Sound absorption value:	up to 48 dB at 7 mm clearance door to floor
Lift height adjustment:	on the release knob with an Allen key 3 mm
Lengths in stock:	585, 710, 835, 960, 1085, 1210, 1335, 1460 mm
Special length:	up to 6000 mm on request
Release:	unilaterally on hinge side
can be shortened:	up to the maximum of 125 mm
Fastening:	laterally with stainless steel angle brackets and screws, incl. floor guide
Stopping plate:	stainless steel, to drive home, 20×20 mm
Floor guide:	included, from plastic with good resistance, with angle brackets and lateral adjustment, screw diameter 4 mm, available with customer
Test approvals:	on request

Very narrow sliding door solution SL with integrated floor guiding groove

Order specifications

- **Planet SL RD/42dB**
Part number 73 xxx*
incl. floor guide, assembly set and
stopping plate type 1, stainless
- **Planet SL FH+RD/42dB**
Part number 74 xxx*
incl. floor guide, assembly set and
stopping plate type 1, stainless

– DIN L or R

*xxx = refer to price list for profile lengths

Accessories / options

- **Planet floor guide SL**
Part number 900 217
- **Installation kit Planet HS**
Part number 900 180
- **Planet Stopping plate** stainless steel
Part number 900 014
- cut the **Planet to fix dimension**
Part number 900 200

Hinge side

Lock side



Planet SL, with retaining bracket, release knob and floor guide


Planet SL, with retaining bracket and floor guide

Planet assembly set HS


Planet floor guide SL



Option:
Planet SL with round-lip



Planet SL assembly DIN R, with floor guide, release on lock side



Planet SL assembly DIN L, with floor guide, release on lock side

SWISS MADE